



**KAMARAJ IAS ACADEMY**  
Only IAS Academy by Grandson of "Perunthalaivar Kamarajar"

# ISRO's Reusable Launch Vehicle Mission RLV LEX

**Published On: 04-04-2023**

**Why is in news?** Recently Indian Space Research Organisation and its partners successfully demonstrated a precise landing experiment for a Reusable Launch Vehicle at the Aeronautical Test Range (ATR), Chitradurga, Karnataka.

**About ISRO's RLV TD project**

?

**Kamaraj IAS Academy**

Plot A P.127, AF block, 6 th street, 11th Main Rd, Shanthi Colony, Anna Nagar, Chennai, Tamil Nadu 600040

Phone: **044 4353 9988 / 98403 94477** / Whatsapp : **09710729833**

# WHAT THE FUTURE HOLDS FOR ISRO

The reusable launch vehicle (RLV) will touch Mach 5 (five times the speed of sound), re-enter atmosphere and land on water



➤ RLV is a winged vehicle that will take off like a rocket and glide back to land like a plane

➤ A developed version of RLV can be used for manned missions in future

➤ In the experiment, RLV will land on water as India does not have a runway of the requisite length of 5km. The longest runway in the country is 2km

## CONVENTIONAL ROCKET

Today, using a conventional rocket, it costs

**\$5,000** to put 1kg of payload in orbit

## REUSABLE LAUNCH VEHICLE



Descent

A reusable vehicle can do the same for **\$500** per kg of payload

**₹300 cr**

India's current annual spend for satellite launches

➤ Exclusive use of RLVs will bring down this cost 10 times

Separated coast phase

Combined coast phase

100 km

Aerodynamic mode

Splashdown

Discarded thruster

Ascent

According to ISRO, the series of experiments with the winged RLV-TD are part of efforts at “developing essential technologies for a fully reusable launch vehicle to enable low-cost access to space”.

The RLV-TD will be used to develop technologies like hypersonic flight (HEX), autonomous landing (LEX), return flight experiment (REX), powered cruise flight, and Scramjet Propulsion Experiment (SPEX).

ISRO's RLV-TD looks like an aircraft. It consists of a fuselage, a nose cap, double delta wings, and twin vertical tails.

**Kamaraj IAS Academy**

Plot A P.127, AF block, 6 th street, 11th Main Rd, Shanthy Colony, Anna Nagar, Chennai, Tamil Nadu 600040

Phone: 044 4353 9988 / 98403 94477 / Whatsapp : 09710729833

The 2016 experiment involved sending a winged spacecraft on a rocket powered by a conventional solid booster (HS9) engine used by ISRO into space.

The spacecraft traveled at a speed of Mach 5 (five times the speed of sound) when re-entering the earth's orbit and traveled a distance of 450 km before splashdown in the Bay of Bengal.

The selection of materials like special alloys, composites, and insulation materials for developing an RLV-TD and the crafting of its parts is very complex and demands highly skilled manpower. Many high technology machinery and test equipment were utilized for building this vehicle

Finally, the first trial of the RLV-TD was conducted on May 23, 2016.

### **RLV technologies at Global level**

Reusable space vehicles have been in existence for a long time with NASA space shuttles carrying out dozens of human space flight missions.

The use case for reusable space launch vehicles has revived with the private space launch services provider Space X demonstrating partially reusable launch systems with its Falcon 9 and Falcon Heavy rockets since 2017. SpaceX is also working on a fully reusable launch vehicle system called Starship.

Several private launch service providers and government space agencies are working on developing reusable launch systems in the world alongside ISRO.

### **History of development of RLV Experiment**

One of the first trials of an RLV was announced by ISRO as far back as 2010, but was put off due to technical reasons. Another was hinted at in 2015 but was again grounded over technical issues.

ISRO's RLV development program took a backseat at the agency as much of the attention in recent years was focussed on the development of the heavy lift Geosynchronous Satellite Launch Vehicle (GSLV) and its high-end version, the GSLV-Mk III, to enable ISRO to break into the lucrative market for launching large communication satellites weighing over 2,000 kg.

When the first experiment was done in 2016, ISRO officials described it as a "baby step" in the development of an RLV. A rocket carrying the 1.75 tonnes RLV-TD was launched into space for 91.1 seconds and reached a height of about 56 km, when the RLV-TD separated from the rocket and climbed to a height of about 65 km.

From this height, the RLV-TD began its return to earth and entered the atmosphere at a speed of around Mach 5 and was navigated by the vehicle's own systems to a predetermined landing spot in the Bay of Bengal, around 450 KM from the launch site at Sriharikota.

The RLV was tracked during the flight from ground stations at Sriharikota and a terminal on a ship. While the re-entry into the earth's atmosphere happens at a velocity of 8 km/sec the RLV TD HEX1 was tested at a much lower velocity of 1.7 km/sec to 2 km/sec. The total flight lasted 770 seconds.

In the first flight, critical technologies such as autonomous navigation, guidance and control, reusable thermal protection system, and re-entry mission management have been successfully validated

### **Second Experiment of RLV-TD**

The experiment was carried out nearly seven years after the technology demonstration of an RLV and the first experiment was conducted successfully by ISRO on May 23, 2016, on the RLV-TD (HEX) mission.

#### **Kamaraj IAS Academy**

Plot A P.127, AF block, 6 th street, 11th Main Rd, Shanthy Colony, Anna Nagar, Chennai, Tamil Nadu 600040  
Phone: **044 4353 9988 / 98403 94477 / Whatsapp : 09710729833**

The recent RLV LEX test involved a Chinook Helicopter of the Indian Air Force lifting the RLV LEX to a height of 4.5 km and releasing the RLV, based on a command from Mission Management Computer

After mid-air release, the RLV carried out an autonomous landing “under the exact conditions of a Space Re-entry vehicle’s landing — high speed, unmanned, precise landing from the same return path — as if the vehicle arrived from space

Landing parameters such as ground relative velocity, the sink rate of landing gears, and precise body rates, as might be experienced by an orbital re-entry space vehicle in its return path, were achieved

According to ISRO, the first test with RLV-TD (HEX1) involved the vehicle landing on a hypothetical runway over the Bay of Bengal while the recent LEX experiment involved a precise landing on a runway

The LEX mission achieved the final approach phase that coincided with the re-entry return flight path exhibiting an autonomous, high speed (350 km per hour) landing

### **Significance of RLV-TD**

With the costs acting as a major deterrent to space exploration, a reusable launch vehicle is considered a low-cost, reliable, and on-demand mode of accessing space.

Nearly 80 to 87 percent of the cost in a space launch vehicle goes into the structure of the vehicle.

The costs of propellants are minimal in comparison. By using RLVs the cost of a launch can be reduced by nearly 80 percent of the present cost

### **Conclusion**

With LEX, the dream of an Indian Reusable Launch Vehicle arrives one step closer to reality .Three more experiments — return flight experiment (REX), powered cruise flight, and Scramjet Propulsion Experiment (SPEX) — have to be conducted.